

Máquina Multifio Skystone Warrior

Technical Parameters								
Parameters Machine type		TSY-MW12	TSY-MW14	TSY-MW32	TSY-MW50	TSY-MW74	TSY-MW80	TSY-MW86
Wire diameter (mm)		Ø7.3	Ø6.3	Ø7.3	Ø7.3	Ø7.3	Ø5.3	Ø5.3
Slab thickness (mm)		20/30/40/50	20/30/40/50	20/30/50/70/80/90	20/30/50/70/80/90	20/30/50/70/80/90	20/30/50/70/80/90	18
Wire quantities (pcs)		12/9/8/6	14/11/9/7	32/24/16/12/11/10	50/38/25/19/17/15	74/55/37/28/25/22	80/60/40/30/27/24	86
Wire length (m)		20	20	20	20	20	20	20
Max cut height (mm)		2200	2200	2200	2200	2200	2200	2200
Max cut width (mm)		348.9	390.3	925.8	1445.7	2136.9	2213.7	2095.5
Max cut length (mm)		3600	3600	3600	3600	3600	3600	3600
Line-speed (m/s)		0–40	0–40	0–40	0–40	0–40	0–40	0–40
Tension (kg)		220–250	190–210	220–250	220–250	220–250	160–170	160–170
Cooling water (L/min)		200	200	500	750	1100	1100	1100
Machine size (m)		8.9'2.6'5.7	8.9'2.7'5.7	9.2'4"5.8	9.8'4.5'5.8	10'7.5'6	10'7.5'6	10'7.5'6
Machine weight (t)		16	16.5	28	42	52	53	53
Main motor power (kW)	kW	75	75	160	225/250	280/315	280	280
Main motor power (hp)	hp	101	101	215	302/335	375/422	375	375
Total power (kW)	kW	82.95	82.95	169.45	236.25/261.25	293.25/328.25	293.25	293.25
Total power (hp)	hp	111	111	227	317/350	393/440	393	393